



# RO13310 Arcbuster welding coverall

**ROSS**  
SAFETY & SURVIVAL

## TICKING ALL BOXES

**PROTECTION LEVEL:  
ARC 2**

**18.0 cal/m<sup>2</sup>**

Above shown is the ATPV value.

## EN SAFETY STANDARDS



Triple stitched



Visible safety standards



EN ISO 13688:2013



EN ISO 11611:2015  
A1 A2 Class 2



EN ISO 11612:2015  
A1 A2 B1 C2 D0 E3 F1



IEC 61482-2:2009  
ATPV 18.0 cal/cm<sup>2</sup>  
Class 1



Internal knee pad pockets

## QUICK DETAIL OVERVIEW

### Available colours

■ Navy ■ Orange

### Product code

RO13310

### Sizing

UK36 - UK60

### Fabric weight

Coverall: 440 g/m<sup>2</sup>

### Inside leg length

Short: 29"  
Regular: 31"  
Tall: 33" (standard size)

This garment is mostly used in > Welding



# RO13310 Arcbuster welding coverall



## FEATURES & BENEFITS

- Concealed heavy-duty jeans closure > Sturdy and out of sight
- 2 internal chest pockets > Safely tuck away your goods
- 2 back pockets with flap > Ambidextrous rear storage space
- 2 side pockets > Ambidextrous storage space
- 1 tool pocket > Extra space for tools
- Internal knee pockets > Stow away your knee pockets internally

## KEY FEATURES



Treated fabric



Visible safety standards



Internal knee pad pockets



Triple stitched

## Related products



**RO8008 - ROOTS knee pads**  
A pair of foam knee pads.

## FABRIC INFORMATION

### Fabric composition

FLC440 - 99% cotton / 1% antistatic

### Fabric weight

440 g/m<sup>2</sup>

### FR Fabric Type

Treated

### Additional certification



- Oeko-Tex Standard 100
- AS/NZ 4399:1996 Sun protective clothing UPF 50+ (Excellent Protection)

Please visit [www.roots-original.com/certificates](http://www.roots-original.com/certificates) to download all relevant certificates.

### Logo

Certified for logo applications

## Product care instructions

To preserve the fabrics strength and protective capacity, we strongly advice to follow our detailed care instructions.

- Always launder with coverall zippers closed.
- Remove all tools from pockets
- Rinse properly after wash.
- Never wash flame retardant clothing with detergents containing bleach.
- After washing, tumble dry at 50°C to avoid excessive shrinkage.
- Do not iron directly over heat seal logos.



Whenever in doubt or in need of advice, ask your dry cleaner or contact us. We are here to help or visit [www.roots-original.com/product-care](http://www.roots-original.com/product-care)



## YOUR ARC FLASH PROTECTION SPECIALISTS

Get in contact, we'd love to help you!

Give us a call on +31 (0)10 2955 955 or drop us a message at: [info@roots-original.com](mailto:info@roots-original.com)