

Anchor strop, 7mm steel, 1m

A100

Steel wire sling with swaged eyes including stainless thimble

Features:

- 7 x 19 steel wire
- PVC protective tube
- Large stainless steel thimbles
- Plastic sleeve on swages
- Individual ID number

Used to provide a durable temporary anchor for rescue systems and access equipment where no fixed anchor points are available. A strong and flexible wire that is hard wearing.

Clear tube which protects the wire structure and allows for visual inspection. Helps minimise slippage on some surfaces.

The large thimbles hold the eyes open and allow rotation of connectors for easier rigging.

Plastic sleeves over the swages protect the user from sharp edges and ends of wire whilst also protecting the label and ID number from dirt and abrasion allowing for longer usable life span.

Options:

- A050 - 50cm
- A100 - 100cm
- A150 - 150cm
- A200 - 200m

Soft eye (identical except without thimbles)


- AS100 - 100cm
- AS150 - 150cm
- AS200 - 200cm

Stainless steel

- ASA100 - 100cm
- ASA150 - 150cm
- ASA200 - 200cm

Stainless steel - soft eye

- ASS100 - 100cm
- ASS150 - 150cm
- ASS200 - 200cm



Specifications:

NB: specifications and colour may change without notice.

Size: 100cm

EN Test Mass: n/a

Loading: WLL 300 kg

Conformity: EN354, EN795(B)

Materials: Galvanised 7 x 19 steel wire rope. Aluminium ferrule, stainless steel thimble. PVC sleeve.

Weight (kg): 0.45

Industries: Used in all forms of work at height and rescue.